U.S. Department of Transportation

Commandant U.S. Coast Guard

2100 Second St S.W.
Washington, DC 20593-0001
Staff Symbol: G-MVI-3
Phone: 202-267-1444

United States Coast Guard

COMDTPUB P16700.4 NVIC 1-94 JANUARY 21, 1994

NAVIGATION AND VESSEL INSPECTION CIRCULAR NO. 1-94

Subj: MARKING OF LIFE PRESERVERS AND PFDs

1. <u>PURPOSE</u> This circular is to be used by vessel operators and Coast Guard marine inspectors to clarify marking requirement changes for life preservers and personal flotation devices (PFDs).

2. BACKGROUND

- a. Present regulations require all life preservers beginning with approval numbers 160.002 or 160.055 to be marked Type I personal flotation device (PFD). Prior to October 1973, most life saving devices were marked either Type I or Type II in addition to an appropriate approval number. Type I meant standard and Type II meant nonstandard construction. Both standard and nonstandard life saving devices approved under 46 CFR 160.002 or 160.055 were for use on inspected vessels.
- b. In October 1973 the current five "performance type" categories listed in enclosure (1) and the term Personal Flotation Device (PFD) were adopted. Only three designation changed, the approval numbers remained the sameerformance Type life preservers currently made to meet carriage requirements on non-SOLAS inspected vessels have approval numbers beginning with 160.002 or 160.055. Devices with approval numbers beginning with 160.004, and 160.005 meet these same carriage requirements, but were never given a type designation and are no longer manufactured. Type designation is documented in enclosure (1), which is a table of equivalents that was in the Code of Federal Regulations until August 6, 1990. This table is still valid. It was deleted only because it was believed to be no longer needed.
- 3. <u>DISCUSSION</u> Recent questions from Officers in Charge, Marine Inspection (OCMIs) indicate some confusion remains concerning the marking of life preservers, life saving devices and PFDs. Specifically, how can an inspector tell if a device manufactured prior to October 1973 is acceptable for use on an inspected vessel? On these older devices, the first part of the approval number is the key to determining their "performance type" documented in enclosure (1). Most flotation devices approved under the old standard / nonstandard "Type" classification have been removed from service due to their deterioration with age and use. However, as the following cases show, some remain in serviceable condition and require particular attention as to their intended use.
 - a. The first case involved a model AK-l, adult life saving device, Approval Number 160.047/324/0. This device is approved as a buoyant vest and marked as Type I. This device is a standard construction performance Type IPFD which is not approved for use on inspected commercial vessels.

- b. The second case involved an adult life preserver, Approval Number 160.055/79/0. This device was approved as a life preserver and marked as Type II. This life saving device is a nonstandard construction performance Type IPFD, which is approved for use on all non-SOLAS commercial vessels.
- 4. <u>IMPLEMENTATION</u> Vessel operators and Coast Guard marine inspectors are to pay particular attention to life preservers and PFDs manufactured prior t~ October 1973 to ensure carriage requirements are met.

R. C. NORTH

U.S. COAST GUARD

ACTING CHIEF, OFFICE OF MARINE SAFETY, SECURITY AND ENVIRONMENTAL PROTECTION

End: (1) Former 33 CFR, Table 175.23 personal flotation device equivalents

- C: e New Orleans (90); Hampton Roads (50); Baltimore (45); San Francisco, Puget Sound (40);
 Philadelphia, Port Arthur, Honolulu (35); Miami, Houston, Mobile, Long Beach, Morgan City (25); Jacksonville, Portland OR (20); Boston, Portland ME, Charleston, Galveston, Anchorage (15); Cleveland (12); Louisville, Memphis, Paducah, Pittsburgh, St. Louis, Savannah, San Juan, Tampa, Buffalo, Chicago, Detroit, Duluth, Milwaukee, San Diego, Juneau, Valdez (10);
 Providence, Huntington, Wilmington, Corpus Christi, Toledo, Guam (5).
- C: m New York (70); St. Ignace (5); Sturgeon Bay (4).
- D:d Except Baltimore and Moriches.
- D:1 CG Liaison Officer MILSEALIFTCOMD (Code N-7CG), CG Liaison Officer RSPA (DHM-22), CG Liaison Officer MARAD (MAR-742), CG Liaison Officer JUSMAGPHIL, CG Liaison Officer World Maritime University, CG Liaison Officer ABS (1).

ABS (260)
Det Norske Veritas (1)
Registro Italiano Navale (1)
NOAA Fleet Inspection Officer (1).
US Merchant Marine Academy (1).

Former Subpart 175.23 Personal flotation device equivalents.

Table 175.23 lists devices that are equivalent to personal flotation devices.

TABLE 175.23

Devices marked—	Are equivalent to performance type
160.002 Life preserver	Type I personal flotation device.
160.003 Life preserver 160.004 Life preserver	Do. Do.
160.005 Life preserver	Do.
160.009 Ring life buoy ¹	Type IV—Personal Flotation Device.
160.047 Buoyant vest	Type II personal flotation device.
160.048 Buoyant cushion	Type IV personal flotation device.
160.049 Buoyant cushion	Do.
160.050 Ring life buoy	
160.052 Buoyant vest	Type II personal flotation device.
160.053 Work vest	Type V personal flotation device.
160.055 Life preserver	Type I personal flotation device.
160.060 Buoyant vest	Type II personal flotation device.
160.064 Special purpose water safety buoyant devices.	A device intended to be worn may be equivalent to type II or type III. A device that is equivalent to type III is marked "Type III Device—may not turn unconscious wearer". A device intended to be grasped is equivalent to type IV.

¹ 46 CFR Subpart 160.009 has been revoked. Type IV PFDs previously approved under that subpart may be used as long as they are in good and serviceable condition.

[CGD 72-120R, 38 FR 8115, Mar. 28, 1973, as amended by CGD 80-155b, 47 FR 10534, Mar. 11, 1982]